

Carrier
One+



www.carriercca.com

Carrier
turn to the experts™





- Auto Restart function
- Active Carbon filter
- LED display
- Turbo & Sleep mode

TECHNICAL SPECIFICATIONS

Indoor Unit Model Number			42KHA009L	42KHA012L	42KHA018L	42KHA024L
Outdoor Unit Model Number			38KHA009LP	38KHA012LP	38KHA018LP	38KHA024LP
Power Supply		Ph-V-Hz	220-230V~ 60Hz, 1Ph	220-230V~ 60Hz, 1Ph	220-230V~ 60Hz, 1Ph	220-230V~ 60Hz, 1Ph
Rating Performance	Nominal Capacity	Btuh	9000	12000	18000	22000
	Input	W	940	1200	1880	2490
	Rating Current	A	4.2	5.4	8.5	11.4
	EER	W/W	2.81	2.93	2.81	2.82
Max. Input Consumption		W	1100	1650	2500	3500
Max. Input Current		A	5.5	8.0	12.9	17.0
Air flow (Hi/Mi/Lo)		m3/h	500/440/330	550/470/400	780/700/550	1050/1000/930
Indoor Sound Level (Hi/Med/Lo)		dB(A)	38/35/29	42/37/34	46/43/40	47/44/41
Indoor Unit	Dimension (WxDxH)	mm	780x285x360	870x285x360	1035x305x380	1120x405x310
	Packing (WxDxH)	mm	780x285x360	870x285x360	1035x305x380	1120x405x310
	Net/Gross Weight	kg	7.0 / 9.0	7.5 / 9.5	10.5 / 13.5	12.5 / 16.0
Outdoor Sound Level		dB(A)	52	53	58	60
Outdoor Unit	Dimension (WxDxH)	mm	681x285x434	700x275x550	770x300x555	845x363x702
	Packing (WxDxH)	mm	795x370x495	815x350x615	910x380x615	985x435x760
	Net/Gross Weight	kg	20.5 / 24.0	25.0 / 28.5	32.0 / 36.5	40.5 / 46.0
Refrigerant Type		g	R410A			
Refrigerant Piping	Liquid Side/Gas Side	mm	Φ6.35/Φ9.52	Φ6.35/Φ12.7	Φ12.7	Φ9.52/Φ15.9
	Max. Pipe Length	m	20	20	25	25
	Max. Difference in Level	m	8	8	10	10



Authorized Distributor: